

## List of material

Rev. 1.0 | 2017-04-24

# Osprey



Description	Article Code	Material	Dimension	Finsih	Manufacturer
Upper sail front	30DMF (WR)	Polyamid 6.6	41 g/m <sup>2</sup>	Coated, water repellent	Dominico Tex. Co.
Upper sail rear	30DMF (WR)	Polyamid 6.6	41 g/m <sup>2</sup>	Coated, water repellent	Dominico Tex. Co.
Lower sail	30DMF (WR)	Polyamid 6.6	41 g/m <sup>2</sup>	Coated, water repellent	Dominico Tex. Co.
Diagonal, loaded and unloaded rib, half rib	9017 E29A	Polyamid 6.6	40 g/m <sup>2</sup>	Coated, water repellent	Porcher Sport
H-Strap bands	9017 E29A	Polyamid 6.6	40 g/m <sup>2</sup>	Coated, water repellent	Porcher Sport
Reinforcement	140 B HTP Opti	Polyester	149 g/m <sup>2</sup>	Coated, Polymer	Dymension Polyant
Rigid rods	-	Plastics	ø 2.0 - 3.0 mm	-	Gin Gliders Inc.
Top, middle and main lines	DSL 70, PPSL 120   200	Dyneema	ø 0.95   1.15   1.42 [mm]	Cover PES	Liros
	TGL 80   400	Aramid	ø 1.1   2.3 [mm]	Cover PES	Gin Gliders Inc.
	7434-280   420	Aramid	ø 1.8   1.2 [mm]	Cover PES	Edelrid
Riser	25-/2mm BLK	Polyester	25mm / 2mm	-	Techni Sangles
Line loop I	Plain Mil-T 5038	Nylon	12 mm	-	Seokwang
Line loop II (brake)	Plain Mil-T 5038	Nylon	10 mm	-	Seokwang
Line shackle (Carabiner)	Shackle	Stainless Steel	ø 3.85 mm	-	JuTech Korea
Speed and Brake pulley	M40011	Nylon		-	
Thread for fabric	Mill Faden 150D/3	Polyester bonded	0.05 g	Impregnated	Amann & Söhne
Thread for riser	210D/4	Polyester bonded	0.07 g	-	Wonang
Trailing Edge Band	6382 X20 (Mylar)	Polyester	10 mm	-	Porcher Sport
Binding Tape (Leading Edge)	Mylar Tape	Nylon	10 mm	-	Seokwang