

*High Performance  
certification EN - C*

**Elan 3  
22 (XS)**  
\*

**Elan 3  
24 (S)**  
\*

**Elan 3  
26 (M)**  
\*

**Elan 3  
28 (L)**  
\*

**Elan 3  
30 (XL)**  
\*

**Elan 3  
33 (XXL)**  
\*

<b>Zoom flat [%]</b>	89	92	0,96	100	104	109
<b>Area flat [m<sup>2</sup>]</b>	22,16	23,68	25,79	27,98	30,26	33,24
<b>Area projected [m<sup>2</sup>]</b>	19,36	20,69	22,52	24,44	26,43	29,04
<b>Span flat [m]</b>	11,86	12,26	12,80	13,33	13,86	14,53
<b>Aspect ratio flat</b>	6,35	6,35	6,35	6,35	6,35	6,35
<b>Root cord [m]</b>	2,35	2,43	2,53	2,64	2,75	2,88
<b>Cells</b>	67	67	67	67	67	67
<b>Weight [kg]</b>	4,60	4,80	5,00	5,20	5,50	5,90
<b>Weight range [kg] *</b>	<b>60-80</b>	<b>75-95</b>	<b>87-105</b>	<b>95-118</b>	<b>105-130</b>	<b>115-145</b>
<b>Min.speed [km/h]</b>	23-25	23-25	23-25	23-25	23-25	23-25
<b>Max.speed [km/h]</b>	38-40	38-40	38-40	38-40	38-40	38-40
<b>Top speed (accelerator) [km/h]</b>	53-55	53-55	53-55	53-55	53-55	53-55
<b>Glide ratio</b>	10,5	10,5	10,5	10,5	10,5	10,5
<b>Min. Sink rate [m/s]</b>	1,05	1,05	1,05	1,05	1,05	1,05
<b>Area projected [m<sup>2</sup>]</b>	19,36	20,69	22,52	24,44	26,43	29,04
<b>Span projected [m<sup>2</sup>]</b>	9,60	9,93	10,36	10,79	11,22	11,76
<b>Aspect ratio projected</b>	4,76	4,76	4,76	4,76	4,76	4,76
<b>Middle line lenght</b>	6,78	7,01	7,32	7,62	7,92	8,31
<b>Total line lenght</b>	222	229	239	249	259	271,5